

REMARKS


Entry of the amendments to the claims and abstract before examination of the application is respectfully requested. These claims patentably define over the art of record.

If there are any questions regarding this Preliminary Amendment or the application in general, a telephone call to the undersigned would be appreciated since this should expedite the prosecution of the application for all concerned.

If necessary to effect a timely response, this paper should be considered as a petition for an Extension of Time sufficient to effect a timely response, and please charge any deficiency in fees or credit any overpayments to Deposit Account No. 05-1323 (Docket # 095309.55774US).

Respectfully submitted,

January 4, 2005


Vincent J. Sunderdick
Registration No. 29,004

CROWELL & MORING LLP
Intellectual Property Group
P.O. Box 14300
Washington, DC 20044-4300
Telephone No.: (202) 624-2500
Facsimile No.: (202) 628-8844
VJS:vlc
#354294

Marked-Up Substitute Specification
Attorney Docket No. 095309.55774US
PCT/EP2003/005964

PIEZOELECTRIC ACTUATOR FOR MEDIA FLOWING THEREAROUND
AND USE OF A CORRESPONDING PIEZOELECTRIC ACTUATOR

[0001] The application claims the priority of German Patent Document No. 102 30 32.1, filed 4 July 2002 and PCT/EP2003/005964, filed 6 June 2003 the disclosure of which is expressly incorporated by reference herein, respectively.

BACKGROUND AND SUMMARY OF THE INVENTION

[0002] The invention relates to a piezoelectric actuator for media flowing therearound ~~according to the precharacterizing clause of claim 1,~~ as disclosed for example by the generically determinative German application DE 198 18 068 A1, and uses of the same.

[0003] The generically determinative German application DE 198 18 068 A1 discloses a piezoelectric actuator for media flowing therearound which comprises a piezo stack which is arranged within a deformable isolating material so as to be in direct contact therewith. The isolating material is ~~for its part~~ enclosed by an actuator housing. The actuator housing is formed by a housing shell, which is connected at ~~its~~ one end to a dimensionally stable actuator top and at ~~its~~ the other end to a dimensionally stable actuator bottom. The actuator top and the actuator bottom are connected to the active main surfaces of the piezo stack. The electrical connecting lines of the piezo stack are led through the actuator top. Furthermore, it is conceivable to lead the actuator connections of the piezo stack up to the end plates (actuator top or actuator bottom) of the actuator and to use one or both end plates as electrical contact surfaces.

[0004] Since the electrically insulating isolating material is formed from an elastic plastic, for example silicone, which bears directly against the outer surface of the piezo stack, it must follow the very rapid movement of the piezo stack in use. As a result, there is the risk of cracks forming in the isolating material and the isolating material becoming detached, so that the medium flowing around can get into the piezo stack in a destructive way.

[0005] The object of the invention is to increase the service life of such actuators for media flowing therearound.

[0006] The object is achieved by ~~an actuator with the features of claim 1.~~ By forming the housing shell from a limp and/or elastic material, ~~with the features claimed,~~ in order that the hermetic separating layer is moved away from the highly active surface of the piezo stack. ~~One of the results of this~~ This is that reduces the effect of wear between the piezo stack, comprising a piezoelectric ceramic, and the isolating material ~~are at least reduced.~~ This is achieved furthermore by simple structural ~~measures~~ operations, so that it is possible to dispense with complex sealing arrangements.

[0007] An actuator according to the invention ~~in this way~~ permits a free change in length of the actuator, or of the piezo stack, with the effect of at least reducing the probability of the piezo stack being wetted by a particularly aggressive medium flowing therearound, preferably a pressurized fuel.

[0008] The housing shell is disposed at a distance from the piezo stack at all points. Furthermore, the length of the housing shell, measured along the

surface line, corresponds at least to the maximum extent of the actuator and/or the housing shell can at least be stretched accordingly, in order that the extent of the piezo stack can be accepted by the housing shell.

[0009] Since the isolating material is preferably formed largely by an incompressible medium, its dimensional change, for example the formation of a constriction in the extent of the piezo stack, can be taken into account in the dimensioning of the length of the housing shell, in particular in the direction of the extent of the piezo stack.

[0010] Furthermore, an electrically insulating fluid, in particular a liquid, and/or a gel is introduced between the housing shell and the piezo stack. The ~~the~~ isolating material, in particular a silicone oil, at least largely ~~filling~~ fills the inside volume of the actuator housing. In this way, the inside volume of the actuator housing is at least largely free from a compressible gas.

[0011] In the case of the claimed construction, only the fluidic isolating material has contact with the piezo stack. Therefore, any shearing forces that may occur ~~here~~ are small, thereby increasing the service life of the actuator. Against this background, it is also ~~of~~ an advantage that, if the isolating material has good to high thermal conductivity, ~~for the removal of~~ any frictional heat occurring between the piezo stack and ~~it~~ the material is removed.

[0012] The same applies to the removal of heat from the piezo stack, for which reason the thermal conductivity of the isolating material is preferably equal to or greater than that of the material of the piezo stack.

[0013] ~~In an advantageous way, the~~ The same advantage applies to the thermal conductivity of the two end plates (actuator top and actuator bottom), whereby the dissipation of the heat occurring in active operation to the medium flowing around is facilitated and/or improved.

[0014] Since the media flowing around the actuator, in particular fuel for the operation of an internal combustion engine, may well have a chemically or in some other way aggressive character, material which is at least largely resistant to these expected stresses ~~that are to be expected~~ is expediently chosen as the material of the housing shell.

[0015] In a favorable way, the viscosity of the isolating medium corresponds approximately to that of the medium flowing around, since the loading of the material of the housing shell by the medium flowing therearound is further reduced as a result.

[0016] In particular when using actuators of which the end plate(s) is/are used as electrical contacts, the material of the housing shell is appropriately an electrically insulating material.

[0017] Depending on the application, for example in hydraulics, it is favorable to form the actuator top with a different cross-sectional area than the actuator bottom. In a ~~way which goes further~~ refinement, the actuator top and/or the actuator bottom has a cross-sectional area which is adapted to the respective conditions in use.

[0018] A preferred use of actuators according to the invention is in and/or as an injection valve, in particular of an internal combustion engine, preferably in a gasoline or diesel engine. Furthermore, such an actuator may also be used for a proportional valve and/or for a sonotrode.

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] ~~Appropriate refinements can be taken from the subclaims.~~
Otherwise, the The invention is explained in more detail on the basis of exemplary embodiments that are represented in the figures, in which:

[0020] Figure 1 shows an exploded representation of an actuator,

[0021] Figure 2 shows an actuator as shown in Figure 1, arranged in a medium and in the relaxed state,

[0022] Figure 3 shows the actuator as shown in Figure 1 in the completely extended state,

[0023] Figure 4 shows an actuator with opened actuator top and electrical lines led out from the actuator housing on one side,

[0024] Figure 5 shows an actuator with electrical lines arranged on both end plates,

[0025] Figure 6 shows an actuator with different end plates and elastic material for the housing shell and

[0026] Figure 7 shows the actuator as shown in Figure 6 with an extended piezo stack.

DETAILED DESCRIPTION OF THE DRAWINGS

[0027] In Figure 1, an exploded drawing of an actuator according to the invention is represented. The actuator has inside it a centrally arranged piezo stack 1 comprising a number of layers of piezo sheets of a piezoelectric ceramic.

[0028] The piezo stack 1 is surrounded by an electrically insulating isolating material 3, in particular a silicone oil. The isolating material 3 is surrounded on the outside by a housing shell 4, which is sealed with respect to the isolating material 3.

[0029] Arranged preferably equidistant from each other on the active main surfaces of the piezo stack 1, there is on the one hand a dimensionally stable actuator top 5b and on the other hand a dimensionally stable actuator bottom 5a.

[0030] The actuator bottom 5a and the actuator top 5b are both connected in a sealing manner to the housing shell 4, with respect to the isolating material 3 and with respect to the medium flowing around. The actuator bottom 5a, the actuator top 5b and the housing shell 4 together form an actuator housing which is sealed at least with respect to the isolating material 3 and the medium flowing around.

[0031] ~~Led to the actuator top 5b are electrical~~ Electrical connecting lines 2, which ~~lead to the actuator 5b~~, are both connected to regions of the actuator top 5b in such a way that they are electrically conducting but nevertheless insulating with respect to each other. One of the connecting lines 2 is

respectively connected to unipolar regions of the piezo sheets. They serve for supplying voltage and for controlling the extent of the piezo stack 1. In this way, the corresponding regions of the actuator top 5b that are connected to these connecting lines 2 represent contact surfaces for the electrical control of the actuator.

[0032] In the present exemplary embodiment, the housing shell 4 consists of a limp, preferably tear-resistant material. It is disposed at a, not necessarily constant, distance from the piezo stack 1 at all points.

[0033] In Figures 2 and 3, the actuator shown in Figure 1 is represented in a fuel for internal combustion engines, preferably gasoline or diesel engines, which is flowing around it and under pressure (see arrows). In the moved-together state, the housing shell 4, made of limp material, is of a form which is irregular and pushed-together or pressed-together axially (along the main direction of extent of the piezo stack 1) and radially (see Figure 2). When the piezo stack 1 is fully extended (see Figure 3), the housing shell 4 is stretched and approximates to a straight line.

[0034] As can be seen, the minimum height of the housing shell 4, measured along the surface line, corresponds at least to the corresponding maximum extent of the actuator. The said minimum height also comprises include compensation for the deformation of the isolating material 3, as may occur at least when the piezo stack extends.

[0035] The deformation of the liquid and/or gel-like isolating material 3, preferably a silicone oil, is based on the incompressibility of fluids. Since the volume of an incompressible isolating material 3 remains the same when the piezo stack 1 extends, it must change its shape. This may take place for example - as represented in Figure 7 - in a constricted manner from one cylindrical shape to another cylindrical.

[0036] It follows ~~from this~~ that the minimum length of the shell is usually somewhat greater than the distance between the two end plates 5 when the piezo stack 1 is completely extended (see Figures 2 and 3). In the case of a purely limp and inelastic material, the compensation should already be taken into account in the dimensioning of the length for the housing shell. In the case of an elastic material, the compensating length and/or the displacement of the piezo stack 1 can be applied in particular just by the elasticity of the material.

[0037] The exemplary embodiment according to Figure 4 is identical in large parts to that shown in the previous figures. The representation is shown however without the actuator top 5b and without isolating fluid. In the case of this exemplary embodiment, however, the control lines 7 are led to the outside through the actuator top 5b - not depicted - and electrically insulated from one another.

[0038] In the exemplary embodiment as shown in Figure 5, on the other hand, one connecting line is connected in an electrically conducting manner to the actuator bottom 5a and the other to the actuator top 5b. In particular in this

case, the housing shell 4 should be produced from an electrically insulating material.

[0039] Represented in Figures 6 and 7 are actuators of which the actuator bottom 5a and actuator top 5b have a different cross section. At the same time, the end plates serve as electrical connections for the piezo stack 1. The housing shell 4 is produced from a material which is electrically insulating and elastic. In the relaxed state (stress equals zero) of the piezo stack 1, the length of the housing shell is greater than the distance between the two end plates 5 connected to them in a sealing manner, so that the housing shell gives a limp impression.

[0040] In the fully extended state of the piezo stack 1 (see Figure 5), the surface line of the housing shell 4 does not run in a straight line between the two end plates 5 but as a constriction, for the reasons stated above.

[0041] With the present elastic material of the housing shell 4, which is additionally also limply fitted, in the case of this exemplary embodiment the compensating length is applied by the greater length of the shell in comparison with the drawn-together position of the piezo stack 1 and also by the elasticity of the material of the housing shell 4.

Abstract of the Disclosure

~~The invention relates to a~~ A piezoelectric actuator for media flowing around it, ~~with having~~ a piezo stack which is arranged within a deformable isolating material so as to be in direct contact therewith at least over certain regions, ~~which~~ The isolating material is ~~for its part~~ enclosed by a fluidically closed actuator housing, which is formed by a housing shell which is delimited at its one end by a dimensionally stable actuator top and at its other end by a dimensionally stable actuator bottom. The actuator top and ~~the actuator~~ bottom are arranged on the active main surfaces of the piezo stack. To increase the service life, the housing shell is produced from a limp and/or elastic material and is disposed at a distance from the piezo stack ~~at all points~~. The length of the housing shell, measured along the surface line, corresponds at least to the maximum extent of the piezo stack and/or the housing shell can be stretched accordingly. ~~Furthermore, the isolating material is an electrically insulating fluid and/or a gel and at least largely fills the inside volume of the sealed actuator housing.~~